



23 Series

CONNECTING THE WORLD

German PDU Sockets

GN2308

- 8ways, 19", 1U standard PDU socket, with switch and cable
- Uninflammable PP module, PVC shell
- 16A, 250V~, MAX3500W, with children protectors
- Gauge: H05VV-F3G1.5mm²×2M+VDE16A plug



GN2308

- 8ways, 19", 1U standard PDU socket, with cable
- Uninflammable PP module, PVC shell
- 16A, 250V~, MAX3500W, with children protectors
- Gauge: H05VV-F3G1.5mm²×2M+VDE16A plug



GN2309

- 9ways, 19", 1U standard PDU socket, with cable
- Uninflammable PP module, PVC shell
- 16A, 250V~, MAX3500W, with children protectors
- Gauge: H05VV-F3G1.5mm²×2M+VDE16A plug



GN2308L

- 8ways, 19", 1U standard PDU socket, with switch and cable
- 16A, 250V~, MAX3500W, with children protectors
- Uninflammable PP module, Aluminium alloy shell
- Gauge: H05VV-F3G1.5mm²×2.15M+VDE16A plug



GN2308L

- 8ways, 19", 1U standard PDU socket, with cable
- 16A, 250V~, MAX3500W, with children protectors
- Uninflammable PP module, Aluminium alloy shell
- Gauge: H05VV-F3G1.5mm²×2.15M+VDE16A plug



GN2309L

- 9ways, 19", 1U standard PDU socket, with cable
- 16A, 250V~, MAX3500W, with children protectors
- Uninflammable PP module, Aluminium alloy shell
- Gauge: H05VV-F3G1.5mm²×2.15M+VDE16A plug



GL2306L

- 6ways, 19", 1U standard PDU socket, With cable and leakage current protector
- 16A, 250V~, MAX3500W, with children protectors
- Uninflammable PP module, Aluminium alloy shell
- Gauge: H05VV-F3G1.5mm²×2.15M+VDE16A plug



GO2326L

- 6ways, 19", 1U standard PDU socket, With cable and double air switch
- 16A, 250V~, MAX3500W, with children protectors
- Uninflammable PP module, Aluminium alloy shell
- Gauge: H05VV-F3G1.5mm²×2.15M+VDE16A plug



GO2316L

- 6ways, 19", 1U standard PDU socket, With cable and single air switch
- 16A, 250V~, MAX3500W, with children protectors
- Uninflammable PP module, Aluminium alloy shell
- Gauge: H05VV-F3G1.5mm²×2.15M+VDE16A plug

