

**GO2826**

- 6ways, 19", 1U standard PDU socket, with cable and double air switch
- 16A, 250V~, MAX3500W, with children protectors
- Uninflammable PC module, Aluminium alloy shell
- Gauge: H05VV-F3G1.5mm<sup>2</sup>×1.8M+VDE16A plug



**GK2815**

- 6ways, 19", 1U standard PDU socket, with cable and master-slave
- 16A, 250V~, MAX3500W, with children protectors
- Uninflammable PC module, Aluminium alloy shell
- Gauge: H05VV-F3G1.5mm<sup>2</sup>×1.8M+VDE16A plug



**GO2816**

- 6ways, 19", 1U standard PDU socket, with cable and single air switch
- 16A, 250V~, MAX3500W, with children protectors
- Uninflammable PC module, Aluminium alloy shell
- Gauge: H05VV-F3G1.5mm<sup>2</sup>×1.8M+VDE16A plug



**GA2807W**

- 7ways, 19", 1U standard PDU socket, with cable, over-loading protector and LED indicator
- 16A, 250V~, MAX3500W, with children protectors
- Uninflammable PC module, Aluminium alloy shell (white)
- Gauge: H05VV-F3G1.5mm<sup>2</sup>×1.8M+VDE16A plug



**GVS2806**

- 6ways, 19", 1U standard PDU socket, with cable, surge protector and switch
- 16A, 250V~, MAX3500W, with children protectors
- Uninflammable PC module, Aluminium alloy shell
- Gauge: H05VV-F3G1.5mm<sup>2</sup>×1.8M+VDE16A plug



**GAS2812**

- 12ways, 1U standard PDU socket, with cable, over-loading protector and switch
- 16A, 250V~, MAX3500W, with children protectors
- Uninflammable PC module, Aluminium alloy shell
- Gauge: H05VV-F3G1.5mm<sup>2</sup>×1.8M+VDE16A plug



**GV2806**

- 6ways, 19", 1U standard PDU socket, with cable and surge protector
- 16A, 250V~, MAX3500W, with children protectors
- Uninflammable PC module, Aluminium alloy shell
- Gauge: H05VV-F3G1.5mm<sup>2</sup>×1.8M+VDE16A plug



**GA2812**

- 12ways, 1U standard PDU socket, with cable, over-loading protector and LED indicator
- 16A, 250V~, MAX3500W, with children protectors
- Uninflammable PC module, Aluminium alloy shell
- Gauge: H05VV-F3G1.5mm<sup>2</sup>×1.8M+VDE16A plug



**GKS2814**

- 5ways, 19", 1U standard PDU socket, with cable, master-slave and switch
- 16A, 250V~, MAX3500W, with children protectors
- Uninflammable PC module, Aluminium alloy shell
- Gauge: H05VV-F3G1.5mm<sup>2</sup>×1.8M+VDE16A plug

