

GO2106-I

- 6ways, 19", 1.5U standard PDU socket, with cable and single air switch
- 16A, 250V~, MAX3500W, with children protectors
- Uninflammable PC module, Aluminium alloy shell
- Gauge: H05VV-F3G1.5mm²×1.8M+VDE16A plug



GVS2106

- 6ways, 19", 1.5U standard PDU socket, with cable, surge protector and switch
- 16A, 250V~, MAX3500W, with children protectors
- Uninflammable PC module, Aluminium alloy shell
- Gauge: H05VV-F3G1.5mm²×1.8M+VDE16A plug



GK2106

- 6ways, 19", 1.5U standard PDU socket, with cable and master-slave
- 16A, 250V~, MAX3500W, with children protectors
- Uninflammable PC module, Aluminium alloy shell
- Gauge: H05VV-F3G1.5mm²×1.8M+VDE16A plug



GO2112-II

- 12ways, 1.5U standard PDU socket, with cable and double air switch
- 16A, 250V~, MAX3500W, with children protectors
- Uninflammable PC module, Aluminium alloy shell
- Gauge: H05VV-F3G1.5mm²×1.8M+VDE16A plug



28 Series

German PDU Sockets

GNS2808

- 8ways, 19", 1U standard PDU socket, with switch and cable
- 16A, 250V~, MAX3500W, with children protectors
- Uninflammable PC module, Aluminium alloy shell
- Gauge: H05VV-F3G1.5mm²×1.8M+VDE16A plug



GN2808

- 8ways, 19", 1U standard PDU socket, with cable and LED indicator
- 16A, 250V~, MAX3500W, with children protectors
- Uninflammable PC module, Aluminium alloy shell
- Gauge: H05VV-F3G1.5mm²×1.8M+VDE16A plug



GAS2807

- 7ways, 19", 1U standard PDU socket, with cable, over-loading protector and switch
- 16A, 250V~, MAX3500W, with children protectors
- Uninflammable PC module, Aluminium alloy shell
- Gauge: H05VV-F3G1.5mm²×1.8M+VDE16A plug



GL2806

- 6ways, 19", 1U standard PDU socket, with cable and leakage current protector
- 16A, 250V~, MAX3500W, with children protectors
- Uninflammable PC module, Aluminium alloy shell
- Gauge: H05VV-F3G1.5mm²×1.8M+VDE16A plug

