

21 Series

IEC PDU Sockets

ENS2108

- 8ways, 19", 1.5U standard IEC PDU, with switch and cable
- 10A, 250V~, MAX2500W
- Uninflammable PC module, Aluminium alloy shell
- Gauge: H05VV-F3G1.5mm²×1.8M+C14plug(VDE16A plug)



EN2109

- 9ways, 19", 1.5U standard IEC PDU, with cable
- 10A, 250V~, MAX2500W
- Uninflammable PC module, Aluminium alloy shell
- Gauge: H05VV-F3G1.5mm²×1.8M+C14plug(VDE16A plug)



EV2107

- 7ways, 19", 1.5U standard IEC PDU, with cable and surge protector
- 10A, 250V~, MAX2500W
- Uninflammable PC module, Aluminium alloy shell
- Gauge: H05VV-F3G1.5mm²×1.8M+C14plug(VDE16A plug)



28 Series

IEC PDU Sockets

ENS28600

- 6×C19, 19", 1U standard IEC PDU, with switch and cable
- 16A, 250V~, MAX3600W
- Uninflammable PC module, Aluminium alloy shell
- Gauge: H05VV-F3G1.5mm²×1.8M+C20plug (VDE16A plug)



EN28600

- 6×C19, 19", 1U standard IEC PDU, with cable and indicator
- 16A, 250V~, MAX3600W
- Uninflammable PC module, Aluminium alloy shell
- Gauge: H05VV-F3G1.5mm²×1.8M+C20plug (VDE16A plug)



ENS2808

- 8×C13, 19", 1U standard IEC PDU, with switch and cable
- 10A, 250V~, MAX2500W
- Uninflammable PC module, Aluminium alloy shell
- Gauge: H05VV-F3G1.5mm²×1.8M+C14plug(VDE16A plug)



EN2808

- 8×C13, 19", 1U standard IEC PDU, with cable and indicator
- 10A, 250V~, MAX2500W
- Uninflammable PC module, Aluminium alloy shell
- Gauge: H05VV-F3G1.5mm²×1.8M+C14plug(VDE16A plug)

