



CSSCR-100

Product Description:

✦ **Features:**

- Elegant design with Acrylic plastic
- Revolutionary products in industry with TCP/IP interface, avoid RS485 communication and low speed for transferring data, standalone or network deployment
- Protect the data with encrypted technology
 - Professional access control function: 50 time zones, 5 groups, 10 open door combination, support multi users entry
- Built-in relay contacts lock, alarm, door sensor & exit button .
- Wiegand input/output enable Master/Slaver access control.



Embedded web server: support browser to inquire access data at local or remote.

- No LCD and no keypad enhance the functions of waterproof and dust proof.
- professional access control software for management

Benefits

- Card Holders: 30,000 cards
- Transaction Capacity: 50,000 events
- Read Range: 5-10 cm
 - Reading Time (Card) :< 30mS
 - Platform: Bio500 (Embedded Linux O/S).
- Communication: RS232/484, TCP/IP.
- Built-in Relay for Door Sensor, alarm, EM-Strike/Magnetic lock, exit button.
- 26 bit Wiegand Input/output.
- LED Indicator: 3 Color LED Indicators(Blue ,Red and Green) with audible beep
 - Blue: Normal standby mode
 - Red: Access denied
 - Green: Access granted
- Power/Current: DC12V/ Max.3 A
- Dimension (W x H x T): 153x95.5x35.5mm
- Operating Temperature: 0°C-45°C
- Operating Humidity:20%-80%
- Optional functions: Mifare/HID/ class card, Web server, Anti-pass back